



Small Indirect Domestic Hot Water Tanks For Air-To-Water Heat Pumps, Geothermal HP, Boilers, Solar Water Heating, and Hydronic Systems

DHW40 All-Stainless Steel w/ Duplex 2205 Inner Tank / 304 Outer Tank Enclosure

Top Quality Indirect DHW Tanks

- 40 Gallons Gross /34 Gallons Net
- 2205 Duplex Stainless Steel Inner Tank
- 316L Stainless Steel Indirect Coil
- Indirect Coil: 1.25" x 33' Convoluted (Wave)
- 304 Stainless Steel Outer Shell
- 2" Thick Polyurethane Insulation
- 1x Element Port, 1" NPSM, Up To 3500W
- 1x Drain Port 3/4" NPT Female
- 2x 1/2" Sensor Wells
- 1x Anode Port w/ Magnesium Anode
- Pressure Drop @7 GPM 4.35 PSI / 10.04 Ft. Head
- Pressure Rating 7 bar (100 psi)
- Cold Inlet 1" NPT
- Hot Outlet 1" NPT
- 1" NPT Coil Connectors
- Tank Diameter 18.5"
- Tank Height 57" + 3" Feet
- Empty Tank Weight 80 Lbs.

Ultra-High Grade
Stainless Steel
Duplex 2205
Inner Tank



Convoluted "Wave" Coil
For Faster Heating

16 Ft² Coil Face
.47 Ft² / Gallon

"Corner-Fit" Design
All Connections On Front

