



Small Indirect Domestic Hot Water Tanks For Air-To-Water Heat Pumps, Geothermal HP, Boilers, Solar Water Heating, and Hydronic Systems

DHW40 All-Stainless Steel w/ Duplex 2205 Inner Tank / 304 Outer Tank Enclosure

Top Quality Indirect DHW Tanks

40 Gallons Gross /36 Gallons Net
 2205 Duplex Stainless Steel Inner Tank
 Indirect Coil: 1.25" x 33' Convuluted (Wave)
 304 Stainless Steel Outer Shell
 2" Thick Polyurethane Insulation
 1x Element Port, 1" NPSM, Up To 3500W
 1x Drain Port ¾" NPT Female
 2x ½" Sensor Wells
 1x Anode Port w/ Magnesium Anode
 Pressure Drop @7 GPM 4.35 PSI / 10.04 Ft. Head
 Pressure Rating 7 bar (100 psi)
 Cold Inlet 1" NPT
 Hot Outlet 1" NPT
 1" NPT Coil Connectors
 Tank Diameter 18.5"
 Tank Height 57" + 3" Feet
 Empty Tank Weight 80 Lbs.

Ultra-High Grade
 Stainless Steel
 Duplex 2205
 Inner Tank



Convoluted "Wave" Coil
 For Faster Heating

16 Ft² Coil Face
 .47 Ft² / Gallon

"Corner-Fit" Design
 All Connections On Front

