



Stainless Steel Domestic Hot Water Tanks For Air-To-Water Heat Pumps, Geothermal HP, Boilers, Solar Water Heating, and Hydronic Systems

Model DHW80 All-Stainless Steel w/ Duplex 2205 Inner Tank / SUS 304 Outer Tank Enclosure


Top Quality Indirect DHW Tanks

- 71 Gallons Net
- 2205 Duplex Stainless Steel Inner Tank
- Indirect Coil: 1.25" x 66' Convolved (Wave)
- SUS 304 Stainless Steel Outer Shell
- 2" Thick Polyurethane Insulation
- 1x Element Port, 1" NPSM, Up To 6000W
- 1x Drain Port 3/4" NPT Female
- 2x 1/2" Sensor Wells
- 1x Anode Port w/ Magnesium Anode
- Pressure Drop @ 7 GPM 6.07 PSI/ 14 Ft. head
- Pressure Rating 7 Bar (101 psi)
- Cold Inlet 1" NPT
- Hot Outlet 1" NPT
- 1" NPT Coil Connectors
- Tank Diameter 23.6"
- Tank Height 64"
- Empty Tank Weight 88 Lbs.

UL 174
CSA 22.2



Ultra-High Grade
Stainless Steel
Duplex 2205



Convolved "Wave" Coil For Faster Heating

