

304 Stainless Steel Multi-Function Tanks For Air-To-Water Heat Pumps, Chillers, and Hydronic/Radiant/Floor Heating Systems

## Vertical or Horizontal Configuration Model VCT60

58 gallons/220 liters

Stainless Steel Inner Tank w/ Stainless Steel Jacket

2" Polyurethane Insulation

2x Element ports 1" NPSM

2x Element/Thermostat Cavities w/ Covers

Supports up to 2x 5500w Elements

6x Side-1 Ports 1.25" NPT Female (3 in /3 out)

4x Side-2 Ports 1.25" NPT Female (2 in / 2 out)

2x Drain Ports ¾" NPT Female (Vertical/Horizontal)

2x G½" Sensor Wells

1x G ¾" Anode Port w/ Anode

2x PG 13.5 Wiring Grommets

Diameter 22.05"


Weight 122 Lbs.

Height 59.84"

otherwise noted ø470 NPT ¾" TPV 3x NPT 1 1/4" Ports 2x Ports PG 13.5 G1 1" NPSM 1265 **Element Port** 1065 965 2x Ports 650 550 180 3x NPT 1 1/4" Ports 380 All Connections Female



Buffer / Multi-Purpose All-Stainless Steel Tank 58 Gallons / 220 L



©2022 Chiltrix Inc

Dimensions: Millimeters unless